Secret Garden Smart Fan

S2432-260H / S2432-510H

32" Ceiling Fan





PRODUCT DESCRIPTION

Drawing inspiration from the serenity of naturalistic design, each luminous Optic Haze crystal bud appears to grow organically into an elegant bramble that winds around the hidden fan blades. The soft luster of the finish and concealed LED illumination enhance this work for art, creating an elevated experience.

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Includes remote control
- Optional wall control sold separately
- · Compatible with Schonbek app

AIRFLOW/ENERGY EFFICIENCY

Weighted-Average/High Airflow CFM: 1600/2600 Weighted-Average/High Energy Use (W): 10/16 **Estimated Yearly Energy Cost (\$):** 5 Weighted-Average/High Efficiency (CFM/W): 105 Max RPM: 395

AVAILABLE FINISHES






French Gold (26) Black (51)

AVAILABLE TRIM



Optic Haze (OH)



SPECIFICATIONS

Construction: Steel Frame, ABS blades Blade: 16° Pitch, 20" sweep .75"W x 4.5"H included Downrod:

Mounting Slope: Up to 30° 80" Wire: **Hanging Weight:** 33 lbs **Total Power:** 36W

Standards: UL/cUL Wet Location listed, Title 24 JA8-2016

Compliant, Title 20, Energy Star rated

Motor Type: 108 x 20 sensorless DC motor

WIRELESS PERFORMANCE

Wi-Fi Range: Up to 150 ft* **Bluetooth Range:** Up to 150 ft*

LUMINAIRE PERFORMANCE

Light Source: LED **Light Wattage:** 20W Lumens/ Delivered Lumens: 1600/1050 Dimming: Integrated CRI: 90 3500K **Color Temperature: Rated Life:** 50,000 hours

The Schonbek app synchronizes seamlessly with smart home devices you already own













Secret Garden Smart Fan

S2432-260H / S2432-510H

32" Ceiling Fan



OPTIONAL ACCESSORIES

OPTIONAL ACCESSORIES				
Bluetooth Wall Control		SF-WCBT	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.
Bluetooth Remote Control	9 9 •	SF-RCBT	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with Moder Forms Smart Fans. Includes easy-to-install wall cradle and batteries.
Downrod		SFDR-12 12IN SFDR-18 18IN SFDR-24 24IN SFDR-36 36IN SFDR-48 48IN SFDR-60 60IN SFDR-72 72IN		All our downrods are .75 (in) and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
Downrod Couplers		SFDC-I		Connects two downrods together.
Sloped Ceiling Kit		SFCK-		Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: Downrod: SFDR-12-26, Downrod Coupler: SFDC-I-26, Sloped Ceiling Kit: SFCK-51

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45° .

NOTE: Recommended maximum downrod length of 72" with 80" lead wire